



Product Name: egger LP/H lacquer

REF: 30601, 30602, 30605, 30606, 30609, 306030

Date of print: 13.11.2023 Date of last alteration: 13.11.2023

egger



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

egger LP/H lacquer

UFI: 207V-A9JN-800P-G5JD

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Ligth curing lacquer for use in audiology.

1.3. Details of the supplier of the safety data sheet

Manufacturer/distributor: egger Otoplastik + Labortechnik GmbH

Street/POB-No.: Aybühlweg 59

Postal code/city/country: 87439 Kempten/Germany

Telephone: +49 831 58113-60

Telefax: +49 831 58113-14

Internet: www.eggeronline.com

E-mail: sales@eggeronline.com

1.4. Emergency telephone number: +49 89 19240

Emergency number: Munich, Germany, (Toxicological dep. of the II. Med. Hospital)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Flam. Liq. 2; H225

Skin Irrit. 2; H315

Eye Irrit. 2; H319

Skin Sens. 1; H317

STOT SE 3; H335

Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazardous components for labelling

"methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate, MMA"

acrylic acid derivatives

@000000030301

vinylester resin

diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

Signal word: Danger

Pictograms:





Product Name: egger LP/H lacquer

REF: 30601, 30602, 30605, 30606, 30609, 306030

Date of print: 13.11.2023 Date of last alteration: 13.11.2023

Hazard statements

H225 Highly flammable liquid and vapour.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.
 H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P501 Dispose of contents/ container in accordance with local and national regulations.

Special labelling of certain mixtures

EUH210 Safety data sheet available on request.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of acrylic/methacrylic resins with auxiliary matters.

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EG) Nr. 1272/2008)			
80-62-6	“methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate, MMA”			40 - < 60 %
	201-297-1	607-035-00-6		
	Flam. Liq. 2, Skin Irrit. 2, Skin Sens. 1, STOT SE 3; H225 H315 H317 H335			
1384855-91-7	2-propenoic acid , reaction products with dipentaerythritol			20 - < 40 %
	800-838-4		01-2119980666-22	
	Eye Irrit. 2, Skin Sens. 1A, Aquatic Chronic 3; H319 H317 H412			
55818-57-0	vinylester resin			0.1 - < 5 %
			01-2119490020-53	
	Skin Sens. 1; H317			
75980-60-8	diphenyl(2, 4, 6-trimethylbenzoyl)phosphine oxide			0.1 - < 5 %
	278-355-8	015-203-00-X	01-2119972295-29	
	Repr. 2, Skin Sens. 1B, Aquatic Chronic 2; H361 H317 H411			

Full text of H and EUH phrases: see section 16.



Product Name: egger LP/H lacquer

REF: 30601, 30602, 30605, 30606, 30609, 306030

Date of print: 13.11.2023 Date of last alteration: 13.11.2023

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
80-62-6	201-297-1	"methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate, MMA"	40 - < 60 %
		inhalation: LC50 = 78 mg/l (vapours); dermal: LD50 = >5000 mg/kg; oral: LD50 = 7870 mg/kg	
1384855-91-7	800-838-4	2-propenoic acid , reaction products with dipentaerythritol	20 - < 40 %
		dermal: LD50 = 2000 mg/kg; oral: LD50 = 2000 mg/kg	
55818-57-0		vinylester resin	0.1 - < 5 %
		dermal: LD50 = >2000 mg/kg; oral: LD50 = >2000 mg/kg	
75980-60-8	278-355-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	0.1 - < 5 %
		dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg	

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Rinse mouth immediately and drink plenty of water.

Seek immediately medical advice. Do not induce vomiting. In case of spontaneous vomiting take care of an unhindered flow out of the vomit (danger of suffocation).

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray jet, Carbon dioxide (CO₂), Foam, Extinguishing powder.

5.2. Special hazards arising from the substance or mixture

Highly flammable. Vapours can form explosive mixtures with air.



Product Name: egger LP/H lacquer

REF: 30601, 30602, 30605, 30606, 30609, 306030

Date of print: 13.11.2023 Date of last alteration: 13.11.2023

egger

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk.

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with: Oxidising agent . Pyrophoric or self-heating substances.



Product Name: egger LP/H lacquer

REF: 30601, 30602, 30605, 30606, 30609, 306030

Date of print: 13.11.2023 Date of last alteration: 13.11.2023

Further information on storage conditions

Keep only in the original container in a cool, dry and well-ventilated place, away from foodstuffs. Keep away from all kind of lighth. An inert gas blanket should not be applied, because the stability of the product depends on the presence of oxygen (air).

7.3. Specific end use(s)

Lacquer for coating of earmoulds. For use by trained specialist staff.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
80-62-6	Methyl methacrylate	50	208		TWA (8 h)	WEL
		100	416		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide			
Worker DNEL, long-term		inhalation	systemic	0,822 mg/m ³
Worker DNEL, long-term		dermal	systemic	0,233 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,145 mg/m ³
Consumer DNEL, long-term		dermal	systemic	0,0833 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,0833 mg/kg bw/day

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Suitable are gloves of the following material: Butyl caoutchouc (butyl rubber).

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.



Product Name: egger LP/H lacquer

REF: 30601, 30602, 30605, 30606, 30609, 306030

Date of print: 13.11.2023 Date of last alteration: 13.11.2023

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
 Colour: light yellow
 Odour: faintly like esters

		Test method
Melting point/freezing point:	not determined	
Boiling point or initial boiling point and boiling range:	92 °C	DIN 51356
Flammability:	not applicable	
Lower explosion limits:	2 vol. %	
Upper explosion limits:	12 vol. %	
Flash point:	12 °C	DIN 51755
Auto-ignition temperature:	>400 °C	DIN 51794
Decomposition temperature:	>100 °C	
pH-Value:	not determined	
Water solubility: (at 20 °C)	16 g/L	
Solubility in other solvents	not determined	
Partition coefficient n-octanol/water:	not determined	
Vapour pressure: (at 20 °C)	40 hPa	
Vapour pressure: (at 50 °C)	160 hPa	
Density (at 20 °C):	1.07 g/cm ³	DIN 51757
Relative vapour density:	not determined	

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

The product is not: Explosive.

Self-ignition temperature

Solid: not applicable

Gas: not applicable

Oxidizing properties

Not oxidizing.

Other safety characteristics

Evaporation rate: not determined

Solid content: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.



Product Name: egger LP/H lacquer

REF: 30601, 30602, 30605, 30606, 30609, 306030

Date of print: 13.11.2023 Date of last alteration: 13.11.2023

10.3. Possibility of hazardous reactions

Reacts with: oxidising agents, radicals forming substances or heavy metal ions.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Ultra-violet light and daylight initiate polymerisation of the product. Therefore keep only in tightly closed containers away from any sources of light. Keep in a refrigerator at 2 °C - 25 °C / 36 °F - 77 °F.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

In case of fire, acrid acrylic fumes may occur.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EG) Nr. 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l;

ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				Method
	Exposure route	Dose	Species	Source	
80-62-6	"methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate, MMA"				
	oral	LD50 7870 mg/kg	Rat		
	dermal	LD50 > 5000 mg/kg	Rabbit		
	inhalative (4 h) vapour	LC50 78 mg/l	Rat		
1384855 -91-7	2-propenoic acid , reaction products with dipentaerythritol				
	oral	LD50 2000 mg/kg	Rat		OECD 423
	dermal	LD50 2000 mg/kg	Rabbit		OECD 402
55818-57-0	vinylester resin				
	oral	LD50 >2000 mg/kg	Rat		OECD 401
	dermal	LD50 >2000 mg/kg	Rat		OECD 402
75980-60-8	diphenyl(2, 4, 6-trimethylbenzoyl)phosphine oxide				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rat		

Irritation and corrosivity

Causes skin irritation. Causes serious eye irritation.

Sensitising effects

May cause an allergic skin reaction. ("methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate, MMA"; 2-propenoic acid , reaction products with dipentaerythritol; vinylester resin; diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide)



Product Name: egger LP/H lacquer

REF: 30601, 30602, 30605, 30606, 30609, 306030

Date of print: 13.11.2023 Date of last alteration: 13.11.2023

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. ("methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate, MMA").

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
80-62-6	"methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate, MMA"					
	Acute fish toxicity	LC50 >100 mg/l	96 h			
1384855-91-7	2-propenoic acid , reaction products with dipentaerythritol					
	Algae toxicity	NOEC 10 mg/l	72 d	Pseudokirchneriella subcapitata		OECD 201
55818-57-0	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide					
	Acute algae toxicity	ErC50 > 2.01 mg/l	72 h	Scenedesmus subspicatus		
	Acute crustacea toxicity	EC50 3.53 mg/l	48 h	Daphnia magna (Big water flea)		
	Acute bacteria toxicity	(EC50 >1000 mg/l)	3 h	Activated sludge		

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
55818-57-0	vinylester resin			
		42 %	28	
	Not readily biodegradable (according to OECD criteria)			
75980-60-8	diphenyl(2, 4, 6-trimethylbenzoyl)phosphine oxide			
		0 - 10 %	28	
	Not readily biodegradable (according to OECD criteria).			



Product Name: egger LP/H lacquer

REF: 30601, 30602, 30605, 30606, 30609, 306030

Date of print: 13.11.2023 Date of last alteration: 13.11.2023

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
55818-57-0	vinylester resin	3.8
75980-60-8	Diphenyl(2, 4, 6-trimethylbenzoyl)phosphinoxid	3.1

BCF

CAS No	Chemical name	BCF	Spezies	Quelle
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	47-55	Cyprinus carpio (Common Carp)	

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

Not identified as PBT/ vPvB substances.

12.6. Other adverse effects

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1866

14.2. UN proper shipping name: Resin solution

14.3. Transport hazard class(es): 3

14.4. Packing group: I

Hazard label: 3

Classification code: F1

Limited quantity: 500 mL

**Product Name: egger LP/H lacquer**

REF: 30601, 30602, 30605, 30606, 30609, 306030

Date of print: 13.11.2023 Date of last alteration: 13.11.2023

egger

Excepted quantity: E3
Transport category: 1
Hazard No: 33
Tunnel restriction code: D/E

Other applicable information (land transport)

Flammable liquid

Marine transport (IMDG)

14.1. UN number or ID number: UN 1866
14.2. UN proper shipping name: Resin solution
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3
Marine pollutant: nein
Special Provisions: -
Limited quantity: 5L/30 kg
EmS: F-E, S-E

Other applicable information (marine transport)

Flash point: 12 °C c.c.

Air transport ((ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1866
14.2. UN proper shipping name: Resin solution
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3
Limited quantity Passenger: 1 L/30 kg
Passenger LQ: Y341
Excepted quantity: E2
IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

14.6. Special precautions for user

Warning: Combustible liquid.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII): Entry 3, Entry 40, Entry 75
Information according to 2012/18/EU
(SEVESO III): P5c FLAMMABLE LIQUIDS

**Product Name: egger LP/H lacquer**

REF: 30601, 30602, 30605, 30606, 30609, 306030

Date of print: 13.11.2023 Date of last alteration: 13.11.2023

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Water contaminating class (D): 2 - obviously hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Abbreviations and acronyms**

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50 %

LD50: Lethal dose, 50 %

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

DNEL: Derived No Effect Level

DMEL: Derived Minimal Effect Level

PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate

LL50: Lethal loading, 50 %

EL50: Effect loading, 50 %

EC50: Effective Concentration 50 %

ErC50: Effective Concentration 50 %, growth rate

NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic

vPvB: very persistent, very bioaccumulative

RID: Regulations concerning the international carriage of dangerous goods by rail

EmS: Emergency Schedules

MFAG: Medical First Aid Guide

ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container

SVHC: Substance of Very High Concern

Flam. Liq: Flammable liquids

Skin Irrit: Skin irritation

Eye Irrit: Eye irritation

Skin Sens: Skin sensitisation

Repr: Reproductive toxicity

STOT SE: Specific target organ toxicity - single exposure

Aquatic Chronic: Chronic aquatic hazard


Product Name: egger LP/H lacquer

REF: 30601, 30602, 30605, 30606, 30609, 306030

Date of print: 13.11.2023 Date of last alteration: 13.11.2023



 egger

Classification for mixtures and used evaluation method according to Regulation(EG) Nr. 1272/2008

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
STOT SE 3; H335	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.
 H361 Suspected of damaging fertility or the unborn child.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.
 EUH210 Safety data sheet available on request.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)