



# Vorläufiges Datenblatt epro<sup>®</sup>-DM.A

## Gehörschutz

(Stand: 04.03.2025)



Dämmwerte:

	SNR <sub>84</sub> [dB]	H <sub>84</sub> [dB]	M <sub>84</sub> [dB]	L <sub>84</sub> [dB]
Result (m <sub>r</sub> s <sub>i</sub> )	15	16	11	11
m <sub>r</sub>	16.6	17.3	13.8	13.5
s <sub>i</sub>	2.0	1.6	2.7	2.8
Limit		12	11	9

epro-DM.A 15

	SNR <sub>84</sub> [dB]	H <sub>84</sub> [dB]	M <sub>84</sub> [dB]	L <sub>84</sub> [dB]
Result (m <sub>r</sub> s <sub>i</sub> )	23	23	22	20
m <sub>r</sub>	24.9	24.2	24.0	23.4
s <sub>i</sub>	1.8	1.6	2.4	3.7
Limit		12	11	9

epro-DM.A 25

	SNR <sub>84</sub> [dB]	H <sub>84</sub> [dB]	M <sub>84</sub> [dB]	L <sub>84</sub> [dB]
Result (m <sub>r</sub> s <sub>i</sub> )	26	30	23	20
m <sub>r</sub>	31.0	33.9	27.9	25.5
s <sub>i</sub>	4.8	4.2	5.1	5.2
Limit		12	11	9

epro-DM.A SWITCH  
closed (max.)

	SNR <sub>84</sub> [dB]	H <sub>84</sub> [dB]	M <sub>84</sub> [dB]	L <sub>84</sub> [dB]
Result (m <sub>r</sub> s <sub>i</sub> )	12	13	9	8
m <sub>r</sub>	13.7	15.0	11.1	10.1
s <sub>i</sub>	1.8	2.1	2.1	2.1
Limit		12	11	9

epro-DM.A SWITCH  
open (min.)

